

ML11i SD

VIDEO	Interfaces	SD/SDI, Analog (Composite)
	Format	PAL/NTSC
	Encoding	H.264 AVC High profile
	Input Resolutions	720i 50
	Output Resolutions	SD, CIF, QCIF
	Bitrate	256 Kbps – 6 Mbps
	Delay	3 sec. – 6 sec. (User can set for more delay)
AUDIO	Interfaces	XLR L/R Balanced
	Intercom	Mic. jack, earphone jack
	Encoding	HE-AAC, AC3
	Bitrate	24 - 96 Kbps
MODEMS	6 embedded 3G/4G LTE modems	
SIM CARDS	6 easy to reach SIM card slots New SIM cards just Plug & Run for abroad using	
RECORDING	Local recording into Transmitter, Each video stream is automatically recorded MPEG-TS format into Receiver.	
CONTROL	Full local monitoring and control using touch screen UI, full remote monitoring and control over the Internet, from Android smart phones.	
OPERATING SYSTEM	Linux OS running on Transmitter and Receiver	
OTHER INTERFACES	1 X RJ45 10/100/1000 Mbps	
	1 X Usb 2.0	
	32GB Micro SD	
TRANSFER	3G/4G LTE, Wi-Fi, Ethernet	
POWER	V-mount battery, 12 V DC, Car charger	
OTHER FEATURES	VBR (Variable bit rate)	
	FEC (Forward error correction)	
	Store & Forward	
	File transfer capability (Both side)	
	Dimension: 18 cm x 22 cm x 6 cm	
	Operating Temperature: -10°C – +45°C	
	Storage Temperature: -40°C – +80°C	
	Weight: 1.4 kg.	
Can easily be carried in a specially designed bag		

